



## Cisco SRW2008 8-Port Gigabit Switch: WebView Cisco Small Business Managed Switches

High-performance, secure switching for small businesses

### Highlights

- Eight high-speed ports to support bandwidth-intensive applications
- Strong security protects network traffic to keep unauthorized users off the network
- Intelligent QoS helps ensure a consistent network experience and supports networked applications including voice, video, and data storage
- Simplified, web-based management for easy installation and configuration

**Figure 1.** Cisco SRW2008 8-Port Gigabit Switch: WebView



### Product Overview

The Cisco® SRW2008 8-Port Gigabit Switch (Figure 1) brings Gigabit speeds to your users while adding intelligence and security to the network. The eight 10/100/1000 Mbps ports enable you to take advantage of the Gigabit Ethernet interfaces shipping in the current generation of servers, workstations, and storage devices, in addition to supporting existing 10/100 Mbps clients. The optional mini Gigabit Interface Converter (mini-GBIC) ports allow you to expand your network as your business grows.

For security, the Cisco SRW2008 incorporates IEEE 802.1 VLANs, IEEE 802.1X port authentication, and MAC-based filtering. The switch also has access control lists (ACLs), which provide more granular security settings as well as improved QoS control through IEEE 802.1p, Differentiated Services (DiffServ), or type of service (ToS) prioritization schemes. The enhanced QoS capability, combined with the SRW2008's advanced traffic-management features, helps ensure clear and reliable voice and video communications.

WebView management software provides an intuitive, secure management interface, enabling you to better utilize the comprehensive feature set of the Cisco SRW2008, for a better-optimized, more secure network.

## Features

- Eight 10/100/1000 Gigabit Ethernet ports
- Two mini-GBIC slots for fiber and copper Gigabit Ethernet expansion
- 16-Gbps, nonblocking, store-and-forward switching capacity
- Simplified QoS management using 802.1p, DiffServ, or ToS traffic prioritization specifications
- ACLs for granular security and QoS implementation
- Configuration and monitoring from a standard web browser with WebView management
- Secure remote management of the switch via Secure Shell (SSH) and SSL encryption
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge (PVE) for simplified network isolation of guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)
- User/network port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate-limiting capabilities and storm control, including multicast, broadcast, and flood control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo frame support (10 KB)
- Simple Network Management Protocol (SNMP) versions 1, 2c, and 3 and Remote Monitoring (RMON) support
- Fully rack mountable using the included rack-mounting hardware

## Specifications

Table 1 contains the specifications, package contents, and minimum requirements for the Cisco SRW2008P 8-Port Gigabit Switch.

**Table 1.** Specifications for the Cisco SRW2008P 8-Port Gigabit Switch: WebView/PoE

Specifications	
<b>Ports</b>	<ul style="list-style-type: none"> <li>• 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T with 2 Gigabit combo ports shared between mini-GBIC ports and ports 7 and 8</li> <li>• Console port</li> <li>• Auto medium dependent interface (MDI) and MDI crossover (MDI-X)</li> <li>• Auto negotiate/manual setting</li> </ul>
<b>Cabling type</b>	<ul style="list-style-type: none"> <li>• Unshielded twisted pair (UTP) Category 5 or better for 10BASE-T/100BASE-TX</li> <li>• UTP Category 5 Ethernet or better for 1000BASE-T</li> </ul>
<b>LEDs</b>	Link/Act, Gigabit speed, System
Performance	
<b>Switching capacity</b>	16 Gbps, nonblocking
<b>Forwarding rate</b>	11.9 mpps wire-speed performance
Layer 2	
<b>MAC table size</b>	8000

<b>Number of VLANs</b>	256 active VLANs (VLAN ID range is 4096)
<b>VLAN</b>	<ul style="list-style-type: none"> <li>• Port-based and 802.1Q tag-based VLANs</li> <li>• Management VLAN</li> </ul>
<b>Head-of-line (HOL) blocking</b>	HOL blocking prevention
<b>Management</b>	
<b>Web user interface</b>	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
<b>SNMP</b>	SNMP versions 1, 2c, and 3 with support for traps
<b>SNMP MIBs</b>	RFC1213 MIB-2, RFC2863 interface MIB, RFC2665 Ether-like MIB, RFC1493 bridge MIB, RFC2674 extended bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1, 2, 3, and 9 only), RFC2737 entity MIB, RFC 2618 RADIUS client MIB RFC 1215 traps
<b>RMON</b>	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis
<b>Firmware upgrade</b>	Web browser upgrade (HTTP) and Trivial File Transfer Protocol (TFTP)
<b>Port mirroring</b>	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe
<b>Other management</b>	<ul style="list-style-type: none"> <li>• Traceroute</li> <li>• SSL</li> <li>• SSH</li> <li>• RADIUS</li> <li>• Port mirroring</li> <li>• TFTP upgrade</li> <li>• SSL security for web user interface</li> <li>• Dynamic Host Configuration Protocol (DHCP) client</li> <li>• BOOTP</li> <li>• Simple Network Time Protocol (SNTP)</li> <li>• Xmodem upgrade</li> <li>• Cable diagnostics</li> <li>• Ping</li> <li>• Telnet client (SSH secure support)</li> </ul>
<b>Security</b>	
<b>IEEE 802.1X</b>	802.1X - RADIUS authentication; MD5 encryption
<b>Access control</b>	ACLs - Drop or rate limit based on: <ul style="list-style-type: none"> <li>• Source and destination MAC-based</li> <li>• Source and destination IP address</li> <li>• Protocol</li> <li>• ToS/DSCP</li> <li>• Port</li> <li>• VLAN</li> <li>• Ethertype</li> </ul>
<b>Availability</b>	
<b>Link aggregation</b>	<ul style="list-style-type: none"> <li>• Link aggregation using IEEE 802.3ad LACP</li> <li>• Up to 8 ports in up to 8 groups</li> </ul>
<b>Storm control</b>	Broadcast, multicast, and unknown unicast
<b>Spanning Tree</b>	<ul style="list-style-type: none"> <li>• IEEE 802.1D Spanning Tree, IEEE 802.1w Rapid Spanning Tree</li> <li>• IEEE 802.1s Multiple Spanning Tree</li> </ul>
<b>Internet Group Management Protocol (IGMP) snooping</b>	IGMP (versions 1 and 2) snooping limits bandwidth-intensive video traffic to only the requestors. Supports 256 multicast groups
<b>QoS</b>	
<b>Priority levels</b>	4 hardware queues
<b>Scheduling</b>	Priority queuing and weighted round-robin (WRR)

<b>Class of service</b>	<ul style="list-style-type: none"> <li>• Port based</li> <li>• 802.1p VLAN priority based</li> <li>• IPv4/v6 IP precedence/ToS/DSCP based</li> <li>• TCP/User Datagram Protocol (UDP) port based</li> <li>• DiffServ</li> <li>• Classification and re-marking ACLs</li> </ul>
<b>Rate limiting</b>	<ul style="list-style-type: none"> <li>• Ingress policer</li> <li>• Egress rate control</li> </ul>
<b>Standards</b>	802.3 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x flow control, 802.3ad LACP, 802.1d Spanning Tree Protocol (STP), 802.1Q/p VLAN, 802.1w Rapid STP, 802.1s Multiple STP, 802.1X port access authentication
<b>Environmental</b>	
<b>Dimensions W x H x D</b>	11 x 1.75 x 6.69 in. (279 x 45 x 170 mm)
<b>Unit weight</b>	2.20 lb (1 kg)
<b>Power</b>	External AC power adapter
<b>Certification</b>	FCC Part 15 Class A, CE Class A, UL, cUL, CE mark, CB
<b>Operating temperature</b>	32° to 104°F (0° to 40°C)
<b>Storage temperature</b>	-4° to 158°F (-20° to 70°C)
<b>Operating humidity</b>	10% to 90%
<b>Storage humidity</b>	10% to 95%
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• Cisco SRW2008P 8-Port Gigabit Switch</li> <li>• AC power adapter and cord</li> <li>• Rack-mounting kit</li> <li>• CD with user guide in PDF format</li> <li>• Registration card</li> <li>• Console cable</li> </ul>	
<b>Minimum Requirements</b>	
<ul style="list-style-type: none"> <li>• Web-based utility: Microsoft Internet Explorer (version 5.5 or later)</li> <li>• Category 5 Ethernet network cables</li> <li>• Operating system: Windows 2000, XP, or later</li> </ul>	
<b>Product Warranty</b>	
5-year limited hardware warranty with return to factory replacement and 90-day limited software warranty	

### Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 5-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to:

<http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at

<http://www.cisco.com/go/warranty>.

### For More Information

For more information on Cisco Small Business products and solutions, visit:

<http://www.cisco.com/smallbusiness>.



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)